## **CENTURION**<sup>TM</sup>

## QEX VACUUM PORCELAIN FURNACE



## **Features:**

- Alphanumeric program names
- · Graphic display
- · Absolute vacuum control
- Continuous step technology
- Advanced temperature control
- Programmable muffle position and speed
- Large, stable work platform (10 cm/4")
- · Quartz spiral muffle
- Closed muffle drying/cooling
- 100 Conventional porcelain programs
- Memory card for program backup, and parameter loading
- User can customize program list
- Programmable idle time for closing muffle

- Programming mode for experimental programs
- InCer card for sintering ceramics (InCeram®)
   Optional
- Security code for program lockingMultilingual (English, Spanish and Italian)
- Auto purge
- "Energy Saver" feature
- · Diagnostics for easy troubleshooting
- · Auto idle mode
- · Power failure and runaway protection
- Internal surge/spike protection
- °C to °F conversion
- Programmable night mode temperature

Dimanaiama

• Full Two-year Warranty

Product Code Number: 100/120 Volt - 9494305, 230 Volt - 9494306

## Specifications Operational

operational	
Ramp rate	200 °C (360 °F)/minute max.
High temperature	1200 °C (2192 °F) max.
Low temperature	800 °C (1472 °F) max.
Time range	59:59 minute max.
Vacuum programmable levels	0-100% and 101% (off,
	programmed level
	and pump on continuously)

Electrical		
Operating range	100-120 VAC	230 VAC
	50/60 Hz	50/60 Hz
Current	13 amps @ 100V	7.2 amps @ 230V
	14.5 amps @ 120	V
Wattage	1740 watts maximum including pump	
Watts to maintain		
1000 °C	Less than 500 watt	s, (without vacuum)

Dimensions	
Muffle open	48cm(19")H x 33cm(13")W
	x 44cm (17.4")D
Muffle closed	33cm(13")H x 33cm(13")W
	x 41cm (16")D
Muffle platform	10 cm (4") diameter
Weight	21 kg (45 lb.)
Shipping weight	25 kg (55 lb.)